

Vanberg Specialized Coatings

VSC Rust Converter Data Sheet



PROFESSIONAL COATINGS

PRODUCT DESCRIPTION:

VSC RUST CONVERTER stops further erosion and rusting of metal buildings, machinery, tools, vehicles, equipment, boats and virtually all metals. When applied, **VSC RUST CONVERTER** chemically converts rust into a black organic compound. A clear acrylic coating is formed. The coating is sufficient to last for years without painting, or it can be painted over using epoxy (ARMORCOAT 65), urethane (V-THANE), latex or oil based paints. Extends the life of anything made of metal.

RECOMMENDED USAGE:

For use by agricultural buildings, industrial plants, schools, institutions, office buildings, homes and farms. Use on vehicles, boats, heavy equipment, metal buildings, tools and virtually any metal surface.

PACKAGING INFORMATION:

Available in 1 gallon (4/CASE)

COVERAGE:

One gallon typically covers up to 500 sq. ft. (General Use)

ADVANTAGES

- Oxidizes corrosion and scale
- Non-Flammable
- Brightens surface
- Highly concentrated and powerful

LIMITATIONS:

- Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container.
- All label warnings must be observed until the container has been commercially cleaned or reconditioned.
- Keep out of reach of children.
- Refer to Material Safety Data Sheet for further safety and handling information.
- Dispose of product in accordance with Federal, State and Local regulations. Use licensed hazardous waste company.
- See individual labels for more caution statements.
- See reverse side for limitations of our liability and warranty.

GENERAL PRODUCT DATA

| FEATURE | ADVANTAGE |
|-----------------------------|------------------------------|
| COLOR | Crème, dries clear |
| ODOR | Mild |
| VISCOSITY | Medium bodied |
| WEIGHT/GALLON | 8.5 +/- .1% |
| % VOLATILE BY VOLUME | 50% |
| pH | 1.0 |
| FLASH POINT | N/A |
| SHELF LIFE | 1 year in unopened container |

PRECAUTIONS:

- Keep out of reach of children.
- Harmful if swallowed.
- May cause irritation to eyes or skin.
- Do not get in eyes, or on skin or clothing.
- Wash thoroughly after handling.
- Remove contaminated clothing and shoes.
- Wash clothing before reuse.
- Thoroughly clean contaminated shoes.

FIRST AID:

- In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention.
- For skin, wash thoroughly with soap and water.
- If swallowed, give water and contact physician.

STORAGE:

PROTECT FROM FREEZING. Store product in an area so as to bring the material to normal room temperature before using. Continuous storage should be between 60°F and 90°F.

SURFACE PREPARATION:

Remove all debris. Soils, oils and other contaminants can be removed by high-pressure cleaning with mild degreaser (if needed). Allow to dry. Clean rusted surface of loose rust flakes (if remaining) with wire brush.

DIRECTIONS:

Shake well. Uniformly apply by brushing, dipping, swabbing, spraying or rolling product evenly over rusted surface. Remove excess. May be applied using equipment designed to spray latex paint. If necessary, when spraying, add up to 3 oz. of water per gallon. Allow to dry completely (1 to 2 hours). A clear hard finish will form. If some rust still appears, an additional amount of VSC RUST CONVERTER can be applied. Surface may be painted or left as is after drying. Do not store at 32°F or below.

CLEANUP: Use soap and water to clean tools and equipment immediately after use.

RESTRICTIONS: Allow product to fully dry before painting the surface.

WARRANTY STATEMENT

Information about VSC products is given to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you will make your own tests to determine the suitability of the product for your particular purpose. As products are often applied or used under conditions beyond our control, VSC cannot guarantee anything but the quality of its products. VSC warrants that its products meet the specifications set forth by VSC, but we reserve the right to change any given specification without prior notice. VSC DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of VSC products constitutes acceptance of the terms of this limited warranty and the terms and the conditions set out in our invoice, contrary provisions of buyer's purchase documents not withstanding. Upon receipt of merchandise, purchaser has 30 days to notify VSC in writing that materials are defective. In the event VSC finds that the product delivered is off specification, VSC will, at its sole discretion, either replace the product or refund the purchase price thereof, and VSC's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of VSC exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. VSC will under no circumstances be liable for special, incidental or consequential damages. This warranty supercedes all other guarantees, whether oral or written, and whether expressed, implied or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals which may cause serious physical injury. Before using, please read the Material Safety Data Sheet and follow all precautions to prevent bodily harm.



VANBERG SPECIALIZED COATINGS
PO BOX 19414
LENEXA, KS 66285-9414

March 30, 2009
Data Sheets/VSC Rust Converter