

# Vanberg Specialized Coatings

## VSC Concrete Seal Data Sheet



---

---

### PROFESSIONAL COATINGS

---

---

#### PRODUCT DESCRIPTION:

This solvent-based acrylic quickly penetrates and provides a thorough, durable seal or finish coating. Very good gloss retention. Resists oils, water vapor, alkali and acids. Seals concrete preventing dusting. Prevents pitting and staining. Does not discolor when exposed to UV light. Because it dries quickly, down time is kept to a minimum.

#### RECOMMENDED USES:

Use on concrete, masonry, stone wash, stone and terrazzo. Excellent for factories, livestock facilities, warehouses, garages, maintenance areas, parking lots, sidewalks, driveways, etc. High traffic areas can be easily recoated and maintained. Should not be used on linoleum, asphalt tile, vinyl asbestos tile, rubber or quarry tile.

#### COVERAGE:

Approximately 400 sq. ft. per gallon.

#### PACKAGING:

- 55-gallon unit (445 lbs)
- 5-gallon unit (37 lbs) #CS510-5
- 1-gallon jugs 4/cs (7.4 lbs.) #CS510-1

#### APPLICATION:

Roller or Spray (Use a metal pump up solvent resistant sprayer with Viton gaskets). Clean up with SOLVENT 101 or Xylol.

#### DOT DESCRIPTION:

PAINT (FLAMMABLE LIQUID)  
3, UN 1263, II

#### HMIS:

Health - 2  
Flammability - 3  
Reactivity - 0

#### NFPA:

Health -  
Reactivity - 0  
Flammability - 3

PHYSICAL PROPERTIES	
FORM	LIQUID
ODOR	AROMATIC SOLVENT
COLOR	COLORLESS
CLARITY	CLEAR
SEDIMENT	NONE
STABILITY	1 YEAR MINIMUM
COLD STABILITY	NOT AFFECTED
BOILING POINT	230°F
pH	N/A
SPECIFIC GRAVITY	.89
POUNDS/GALLONS	7.4
SOLIDS	15.0
FLASH POINT	45°F
COVERAGE	300-400 sq. ft./gal.

---

#### WARRANTY STATEMENT

Information about VSC products is given to the best of our knowledge, based on tests and experience. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you will make your own tests to determine the suitability of the product for your particular purpose. As products are often applied or used under conditions beyond our control, VSC cannot guarantee anything but the quality of its products. VSC warrants that its products meet the specifications set forth by VSC, but we reserve the right to change any given specification without prior notice. VSC DISCLAIMS ALL WARRANTIES RELATING TO THE PRODUCTS AND THEIR APPLICATION, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Receipt of VSC products constitutes acceptance of the terms of this limited warranty and the terms and the conditions set out in our invoice, contrary provisions of buyer's purchase documents notwithstanding. Upon receipt of merchandise, purchaser has 30 days to notify VSC in writing that materials are defective. In the event VSC finds that the product delivered is off specification, VSC will, at its sole discretion, either replace the product or refund the purchase price thereof, and VSC's choice of one of these remedies is the buyer's sole remedy. In no event shall the liability of VSC exceed the purchase price of shipped merchandise. Claims must be in writing. Claims after 30 days are void. VSC will under no circumstances be liable for special, incidental or consequential damages. This warranty supercedes all other guarantees, whether oral or written, and whether expressed, implied or statutory. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Certain products may contain chemicals which may cause serious physical injury. Before using, please read the Material Safety Data Sheet and follow all precautions to prevent bodily harm.



**VANBERG SPECIALIZED COATINGS**  
PO BOX 19414  
LENEXA, KS 66285-9414

August 8, 2012  
Data Sheets/VSC Concrete Seal