



# CON-KORITE PLUS REPAIR & OVERLAY MORTAR



## Coverage

20.5 sq. ft. (1.9 m<sup>2</sup>) at 1/4" (.64 cm) per 60 lb. (27.21 kg) batch

## Applications

### Agricultural Uses

- Feed Bunks
- Mangers
- Parlors
- Floors
- Walls
- Troughs
- Gutters

### Industrial & General Uses

- Plant Floors
- Parking Ramps
- Roadways
- Walkways
- Driveways
- Concrete Tanks
- Pot Holes

## Easy to Install

- 1 Prepare Surface  
Mechanical or  
Chemical
- 2 Blend Components



- 3 Place Mortar



- 4 Spread Mortar




or notched trowel

- 5 Finish



- 6 Non-Slip Broadcast



Optional

Can diamond grind and top-coat finished repair surface.

# REPAIR

CON-KORITE PLUS is a 'pure cement' fast-setting, extra abrasion resistant, high strength and non-shrink mortar. It can be used for floor overlays and grouting.

When mixed with *KB25 Acrylic Resin*, this Pure Cement repair or overlay delivers very good resistance to wear and attack by corrosive compounds.

## PACKAGING

### CON-KORITE PLUS

Contains 55 lb. bag mortar,  
2 Qt KB25, 1 Set Control  
PLUS Kit #KB0100

### INDIVIDUAL COMPONENTS

55 lb. Bag #KB0060  
1 Gal. KB25 #KB0026  
5 Gal. KB25 #KB0027

## Provides

- Fast setting - Ready for use within 2-3 hours at 70°F
- Water, Salt & Sulfate tolerant - Withstands tough conditions
- Exceptional abrasion resistance - Stands up to heavy traffic
- Interior/Exterior use - Tolerates all weather conditions
- Non-shrink - Minimizes risk of delamination, improves bond
- High strength - 3 to 5 times stronger than Portland products

