



# CON-KORITE SSL SEMI SELF-LEVELING REPAIR & OVERLAY MORTAR



## Coverage

20 sq. ft. (1.85 m<sup>2</sup>) at 1/4" (.64 cm) per 44 lb. (20 kg) batch

## Applications

### Agricultural Uses

- Feed Bunks
- Mangers
- Parlors
- Floors
- Slats
- Troughs
- Gutters

### Industrial & General Uses

- Plant Floors
- Parking Ramps
- Roadways
- Walkways
- Driveways
- Concrete Tanks
- Pot Holes

## Easy to Install

- 1 Prepare Surface  
Mechanical or Chemical
- 2 Blend Components



- 3 Pour on Repair Area



- 4 Spread Mortar



- 5 Spike Roll



- 6 Non-Slip Broadcast



Optional  
Can diamond grind and top-coat finished repair surface.

# REPAIR

CON-KORITE SSL is a fast-setting, extra abrasion resistant, leveling and low-shrink mortar. It can be used as an interior/exterior patching material, floor overlays, and to level concrete surfaces.

When mixed with *KB25 Acrylic Resin*, this Pure Cement repair or overlay delivers very good resistance to wear and attack by corrosive compounds.

## PACKAGING

### CON-KORITE SSL KIT

Contains 44 lb. (20kg) bag mortar and 1 Gal. (3.8L) KB25  
SSL Kit #KB0040

### INDIVIDUAL COMPONENTS

44 lb. (20kg) batch requires 1 Gal. (3.8L) KB25  
44 lb. (20kg) Bag #KB0040  
1 Gal. (3.8L) KB25 #KB0026  
5 Gal. (19L) KB25 #KB0027

## Provides

- Fast setting - Ready for use within 2-3 hours at 70°F
- Water, Salt & Sulfate tolerant - Withstands tough conditions
- Exceptional abrasion resistance - Stands up to heavy traffic
- Interior/Exterior use - Tolerates all weather conditions
- Non-shrink - Minimizes risk of delamination, improves bond
- High strength - 3 to 5 times stronger than Portland products

